




# TECHNICAL DATA SHEET

Type no.	514 00/AUX 14	
Article no.	025514000101	
Standards	DIN EN 50342-1, 50342-2	
Application	Starter battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	12 Ah (K20)	
Cold start current	200 A (EN)	
<b>Dimensions and weights</b>		
Box	AUX14	
Length max.	150mm	
Width max.	88mm	
Box height max.	145mm	
Total height max.	145mm	
Battery weight	Ca. 4,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,32 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	195	
Pallet ID	Euro pallet	
Items per layer	65	
 Symbolpicture		
<b>Features</b>		
Base hold-down	B00	
Layout	1	
Terminal	S10	
Separator	AGM separator	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
<b>Maintenance 1)</b>		
Water consumption	< 1g/Ah	
Refill water		
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/20 of the rated capacity	
Charging voltage 2)	max. 14,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.  
original