



TECHNICAL DATA SHEET

Type no.	632 11
Article no.	010632110101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	132 Ah (K20)
Cold start current	900 A (EN)
Dimensions and weights	
Box	
Length max.	508mm
Width max.	174mm
Box height max.	205mm
Total height max.	205mm
Battery weight	Ca. 36,0 kg (+/- 5 %)
	
Symbolpicture	
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	24
Pallet ID	Euro pallet
Items per layer	8
Features	
Base hold-down	B1
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Maintenance ¹⁾	
Water consumption	< 1,5g/Ah
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 5 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,4 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original