



TECHNICAL DATA SHEET

Type no.	066 12
Article no.	010066120101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery
Electrical data	
Rated voltage	6V
Rated capacity	66 Ah (K20)
Cold start current	360 A (EN)
Dimensions and weights	
Box	
Length max.	178mm
Width max.	175mm
Box height max.	166mm
Total height max.	188mm
Battery weight	Ca. 9,0 kg (+/- 5 %)
	
Symbolpicture	
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	96
Pallet ID	Euro pallet
Items per layer	24
Features	
Base hold-down	B4
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Maintenance ¹⁾	
Water consumption	> 4g/Ah
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 9 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 6,9 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original