



TECHNICAL DATA SHEET

Type no.	725 11
Article no.	010725110101
Standards	DIN EN 50342-1, 50342-2
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	225 Ah (K20)
Cold start current	1050 A (EN)
Dimensions and weights	
Box	C
Length max.	517mm
Width max.	273mm
Box height max.	212mm
Total height max.	240mm
Battery weight	Ca. 59,0 kg (+/- 5 %)
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	18
Pallet ID	Euro pallet
Items per layer	6
Features	
Base hold-down	B00
Layout	3
Terminal	1
Separator	PE bag separator with glass nonwoven
Degassing	Battery with single degassing
Flame arrester	Not integrated
Maintenance ¹⁾	
Water consumption	> 4g/Ah
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 9 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 13,8 V



Symbolpicture

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.
original